






MANUAL GLASS CUTTING: Oil Lubricating Glass Cutters

In choosing Talamoni, you can select from a wide range of manual glass cutting tools. We have years of experience with oil lubricating hand glass cutters. Our tungsten carbide heads allow the oil to flow to the wheel and axle gliding the cutting stroke along the glass.

Oil Hand Glass Cutters

	Part No. [Model]	Glass Thickness	Description
	OSCUT-L [Ossolaglass Light]	2–10 mm	OSCUT-L has a plastic oil-containing handle which continuously lubricates the cut. A precision cut is created by the diamond wheel's special lapping. The head rotates 360° making it easy to change direction. This self-lubricating glass cutter ensures a smooth break in your glass. Straight edge standoff distance 2.5 mm.
	OSCUT-B [Ossolaglass Big]	2–10 mm	OSCUT-B has a plastic oil holding handle with a diamond cutting wheel with a DSG (double sharpened grind) ensuring a precision cut without exerting much pressure. The head rotates 360° making it easy to change direction. This self-lubricating glass cutter ensures a smooth break in your glass. Straight edge standoff distance 2.5 mm.
	SICUT-L [Simplonglass Light Blue]	2–10 mm	SICUT-L has a sturdy oil containing aluminum handle and is equipped with a quality tungsten carbide wheel that delivers a precision cut while the oil ensures smooth rotation of the wheel. The head rotates 360° for easy direction changes. Straight edge standoff distance 2.5 mm.
	SICUT-DSG [Grey]		SICUT is an aluminum oil container handle glass cutter, equipped with a fixed head and special diamond wheel for cutting coated and ceramic glass. Straight edge standoff distance 2.5 mm.
	VB-CUT [Verbaniaglass]	2–10 mm	The Verbaniglass hand glass cutter has a transparent plastic handle with oil reservoir. A precision cut is created by the diamond wheel's special lapping. The handle design has a flattened end at the top, which helps with opening the cut. The head rotates 360° for easy direction changes. Straight edge stand-off distance 2.5 mm.